

COLOUR STRIKE

Series: Carpet Tile Series

Collection: COLOUR STRIKE TL22



SPECIFICATIONS

CONSTRUCTION	Tufted multi-level loop Pile
PILE FIBRE	100% Recycled Nylon 6
DYED METHOD	Solution Dyed
TUFTING GAUGE	1/10" Inch
PILE WEIGHT	770gm/sqm (22.7oz/yd2) ±5%
PILE HEIGHT	4.5mm(0.177inch)
PRIMARY BACKING	Non- Woven Polyester
BACKING STRUCTURE	Soft Back Lite
BACKING OPTIONS AVAILABLE	EnviraSoft™ Made to order -Consult our representative
TILE SIZE	500mm x 500mm
CASTOR CHAIR RATING	BS EN 985, Passes >2.4 Continuous use (Under-chair mats recommended)
THERMAL RESISTANCE	R Value = 0.08(m2K/W)
ELECTROSTATIC PROPERTIES	CNS 13595 10 ≤2.0KV 20% R.H.at 70 F

PERFORMANCE

WEAR CLASSIFICATION	ACCS Contract Extra Heavy Duty Label No 15100
ENVIRONMENTAL CERTIFICATION	ACCS ECS Level 4
GREEN STAR LEVEL A	Min 7 Credit points
NATIONAL DISABILITY	Compliant

FLAMMABILITY

HOT METAL NUT	BS4790: Hot Metal Nut, Method 1 Pass
RADIANT PANEL TEST	ASTM E648, Class 1
SMOKE DENSITY	189 %. min