

CORAL REEF

Series: Carpet Tile Series

Collection: COLOUR REEF 24CP GB



SPECIFICATIONS

CONSTRUCTION	Tufted multi-level loop Pile
PILE FIBRE	100% Recycled Nylon 6
DYED METHOD	Solution Dyed
TUFTING GAUGE	1/10" Inch
PILE WEIGHT	800gm/sqm (24oz/yd2)
PILE HEIGHT	6.5mm
PRIMARY BACKING	Non- Woven Polyester
BACKING STRUCTURE	Soft Back Deluxe. Acoustic Cushion 4mm
BACKING OPTIONS AVAILABLE	Soft Back Lite (Made to Order) - Consult our representative
TILE SIZE	250mm x 1000mm
CASTOR CHAIR RATING	BS EN 985, Passes >2.4 Continuous use (Under-chair mats recommended)
THERMAL RESISTANCE	R Value = 0.15(m2K/W)
ELECTROSTATIC PROPERTIES	CNS 13595 10 ≤2.0KV 20% R.H.at 70 F

PERFORMANCE

WEAR CLASSIFICATION	Contract Extra Heavy Duty Label No
ENVIRONMENTAL CERTIFICATION	ACCS ECS Level 4
GREEN STAR LEVEL A	Min 7 Credit points
NATIONAL DISABILITY	Compliant

FLAMMABILITY

HOT METAL NUT	BS4790: Hot Metal Nut, Method 1 Pass
RADIANT PANEL TEST	ASTM E648, Class 1
SMOKE DENSITY	370 %. min
RADIANT HEAT SOURCE	AS ISO 9239.1.2003 CHF 4.9K/W/ M2

ACOUSTIC BEHAVIOUR

ACOUSTIC WEIGHTED ABSORPTION COEFFICIENT	EN ISO 34 and EN ISO 11654: αw=0.41(H)
--	--

WARRANTY

WEAR WARRANTY	15 Years Limited Wear Warranty
---------------	--------------------------------