

SURBITON

Series: Carpet Tile Series

Collection: SURBITON TL22GB



SPECIFICATIONS

CONSTRUCTION	Tufted multi-level loop Pile
PILE FIBRE	100% Recycled Nylon 6
DYED METHOD	Solution Dyed
TUFTING GAUGE	1/10" Inch
PILE WEIGHT	770gm/sqm (22.7oz/yd2) ±5%
PILE HEIGHT	4.5mm(0.177inch)
PRIMARY BACKING	Non- Woven Polyester
BACKING STRUCTURE	Soft Back Deluxe. Acoustic Cushion 4mm
BACKING OPTIONS AVAILABLE	Soft Back Lite
TILE SIZE	500mm x 500mm
CASTOR CHAIR RATING	BS EN 985, Passes >2.4 Continuous use (Under-chair mats recommended)
THERMAL RESISTANCE	R Value = 0.15(m2K/W)
ELECTROSTATIC PROPERTIES	CNS 13595 10 ≤2.0KV 20% R.H.at 70 F

PERFORMANCE

WEAR CLASSIFICATION	ACCS Contract Extra Heavy Duty Label No15056 & Label No 15093
ENVIRONMENTAL CERTIFICATION	ACCS ECS Level 4
GREEN STAR LEVEL A	Min 7 Credit points
NATIONAL DISABILITY	Compliant

FLAMMABILITY

HOT METAL NUT	BS4790: Hot Metal Nut, Method 1 Passs
RADIANT PANEL TEST	ASTM E648, Class 1
SMOKE DENSITY	246 %. min
RADIANT HEAT SOURCE	AS ISO 9239.1.2003 CHF 5.2K/W/ M2

ACOUSTIC BEHAVIOUR

ACOUSTIC WEIGHTED ABSORPTION COEFFICIENT	EN ISO 34 and EN ISO 11654: αw=0.41(H)
--	--

WARRANTY

WEAR WARRANTY	15 Years Limited Wear Warranty
---------------	--------------------------------